



ADATTO RM

Surface/Recessed Edge-Lit Running Man



Black Semi-Recessed

Project Name: _____

Model Number: _____

Prepared By: _____

Date: _____

FEATURES & BENEFITS

- Edge-lit LED technology
- Universal surface wall mounting: end, ceiling, or pivoting
- 120-347 VAC Input
- Temperature: 10 °C to 40 °C
- AC/DC
 - 120V / 0.03A / 2.50W, 277V / 0.03A / 2.50W, 347V / 0.03A / 2.50W max power consumption
 - Emergency DC wattages as follows: 6, 12, 24V DC
- Self-Powered
 - 120V / 0.038A / 3W, 277V / 0.038A / 3W, 347V / 0.038A / 3W max power consumption
 - High-performance, sealed Ni-Cad battery
 - 120 minutes emergency duration
 - Solid state transfer and battery charger
- Certified CSA 22.2 No. 141 & Energy Efficiency CAN/CSA-C860

EXTERNAL SPECIFICATIONS

- Chassis, backbox and painted finish trims are constructed of galvanized steel; other finish trims and backboxes are made from high grade aluminum
- All electronics and faceplate mounted to single chassis for rapid and simple installation
- Separate backbox/housing can be pre-installed any time prior to faceplate and electronics
- Hanger bars for drywall ceilings or walls included. (Max. extension of 540 mm)
- Transformer driven. Compatible with generators and inverters

ORDERING GUIDE

AD-RM - - - - -

SERIES	OPERATION	LIGHT SOURCE	FACE #	PICTOGRAM	MOUNTING	OPTIONS
AD-RM	UDC (Universal DC - 6-24VDC) SP (120 minutes self-powered)	L (LED)	1 (Single)	OLR (Universal Pictogram) O (No Indicator) L (Left Indicator) R (Right Indicator) D (Down Indicator) U (Up Indicator) UR (45° Up Right) DR (45° Down Right) UL (45° Up Left) DL (45° Down Left)	M (Universal mount) RC - Fully recessed	WHT (White - Standard) BLK (Black) BA (Brushed Aluminum)
			2 (Double)	O (No Indicator) LR (Left & Right Indicators) D (Down Indicator) U (Up Indicator) UR (45° Up Right) DR (45° Down Right) UL (45° Up Left) DL (45° Down Left)		

ACCESSORIES	ORDERING CODE	DESCRIPTION
FIBER	FIBER-TA-1F-O	RUNNING MAN SINGLE FACE NO ARROW
	FIBER-TA-1F-L	RUNNING MAN SINGLE FACE ARROW LEFT
	FIBER-TA-1F-R	RUNNING MAN SINGLE FACE ARROW RIGHT
	FIBER-TA-2F-O	RUNNING MAN DOUBLE FACE NO ARROW
	FIBER-TA-2F-LR	RUNNING MAN DOUBLE FACE LEFT & RIGHT ARROW
BACK BOX	BBX-SR-WHT-UDC	SEMI RECESSED WHITE BACK BOX UNIVERSAL DC
	BBX-SR-BLK-UDC	SEMI RECESSED BLACK BACK BOX UNIVERSAL DC
	BBX-SR-BA-UDC	SEMI RECESSED BRUSHED ALUMINUM BACK BOX UNIVERSAL DC
PENDANT MOUNTING	PM-EDGLT	PENDANT MOUNT



ADATTO RM

Surface/Recessed Edge-Lit Running Man

PRE-BUILT INVENTORY

ORDERING CODE	SHORT DESCRIPTION	LONG DESCRIPTION
200000001-431	AD-RM-UDC-L-1-0-M-WHT	ADATTO RUNNING MAN EDGELIT SIGN SERIES UNIVERSAL DC WHITE LED SINGLE FACE NO INDICATOR UNIVERSAL MOUNT WHITE FINISH 120-347V INPUT
200000001-432	AD-RM-SP-L-1-0-M-WHT	ADATTO RUNNING MAN EDGELIT SIGN SERIES 120MIN SELFPOWERED WHITE LED SINGLE FACE NO INDICATOR UNIVERSAL MOUNT WHITE FINISH 120-347V INPUT
200000001-433	AD-RM-UDC-L-1-L-M-WHT	ADATTO RUNNING MAN EDGELIT SIGN SERIES UNIVERSAL DC WHITE LED SINGLE FACE LEFT INDICATOR UNIVERSAL MOUNT WHITE FINISH 120-347V INPUT
200000001-434	AD-RM-SP-L-1-L-M-WHT	ADATTO RUNNING MAN EDGELIT SIGN SERIES 120MIN SELFPOWERED WHITE LED SINGLE FACE LEFT INDICATOR UNIVERSAL MOUNT WHITE FINISH 120-347V INPUT
200000001-435	AD-RM-UDC-L-1-R-M-WHT	ADATTO RUNNING MAN EDGELIT SIGN SERIES UNIVERSAL DC WHITE LED SINGLE FACE RIGHT INDICATOR UNIVERSAL MOUNT WHITE FINISH 120-347V INPUT
200000001-436	AD-RM-SP-L-1-R-M-WHT	ADATTO RUNNING MAN EDGELIT SIGN SERIES 120MIN SELFPOWERED WHITE LED SINGLE FACE RIGHT INDICATOR UNIVERSAL MOUNT WHITE FINISH 120-347V INPUT
200000001-437	AD-RM-UDC-L-2-0-M-WHT	ADATTO RUNNING MAN EDGELIT SIGN SERIES UNIVERSAL DC WHITE LED DOUBLE FACE NO INDICATOR UNIVERSAL MOUNT WHITE FINISH 120-347V INPUT
200000001-438	AD-RM-SP-L-2-0-M-WHT	ADATTO RUNNING MAN EDGELIT SIGN SERIES 120MIN SELFPOWERED WHITE LED DOUBLE FACE NO INDICATOR UNIVERSAL MOUNT WHITE FINISH 120-347V INPUT

DIMENSIONS

