



# BOLLA UNIT

Compact Die-cast Aluminum Battery Unit

Project Name: \_\_\_\_\_ Model Number: \_\_\_\_\_  
 Prepared By: \_\_\_\_\_ Date: \_\_\_\_\_

## FEATURES & BENEFITS

- Die-cast aluminum housing
- 6V 36W or 12V 60W
- Clear polycarbonate lens
- Performance optics allows greater spacing between units
- Vandal resistant optional
- Standard white colour with custom colour options
- Surface wall or ceiling mounting
- Suitable for indoor installations
- Operating temperature: +10°C to +40°C
- CSA G22.2 No. 141-15 Performance Certified


## BATTERY TECHNOLOGY

The unit is designed with either a maintenance free, sealed valve regulated lead acid battery or a Ni-MH battery that provides a minimum emergency duration of 30 minutes. Recharge time of the battery is less than twenty-four [24] hours.

## BELUCE AUTO-TEST (AT)

The BeLuCe auto-test system automatically performs one 5 minute discharge test monthly and every 6 months it performs two 30 minute discharge tests, 24 hours apart. This tests both full battery capacity and recharge capability.

## DIMENSIONS



## ORDERING GUIDE

BOL -  -  -  -

SERIES	CAPACITY	LAMP #	LAMP TYPE	OPTIONS
BOL	6V36W (6VDC, 36W) (Lead-acid) 12V60W (12VDC, 60W) (Ni-MH)	1 (Single lamp) 2 (Double lamp)	See lamp selection	AT (Auto-test) WG (Wireguard) TP (Tamper proof screws) CC (Custom colour housing) LC (Line cord) TLP (Twist lock plug)

## LAMP SELECTION

	6V	12V
MR16	N/A	50W*
LED	5, 7W	2, 5, 7W

\*single lamp only

## MODEL RATING GUIDE

MODEL	VOLTAGE (OUTPUT)	VOLTAGE 30MIN	VOLTAGE 90MIN
BOL-6-36	6	36	12
BOL-12-60	12	60	28