



BRUNO RM

Universal Edge-Lit Running Man

Project Name: _____ Model Number: _____
 Prepared By: _____ Date: _____

FEATURES & BENEFITS

- Universal surface or recessed, wall or ceiling end mounting
- Thin profile
- Edge-lit LED technology
- CSA 22.2 No. 141-15 Performance Certified



Recessed Mount



Wall Mount

UNIVERSAL PICTOGRAMS

The OLR(Universal) option includes: a pictogram with no directional indicators, a pictogram with a left facing directional indicator and a pictogram with a right facing directional indicator.



EXTERNAL SPECIFICATIONS

The BRUNO RM housing is constructed from durable die-cast aluminum. The acrylic faceplate is universal and can be configured for both single face or double face. The BRUNO allows the installer to choose between surface or recessed, wall, ceiling or end mounting. The housing comes in a white, baked powder coat finish. Available in custom powder coat finishes or alternate metal finishes (please specify). External LED monitor light and test switch are standard on self-powered versions.

INTERNAL SPECIFICATIONS

AC ONLY, AC/DC and SELF-POWERED comes standard configured with high-output LED technology, 120/347VAC input (optional 120/277V). Nickel-cadmium batteries provide a minimum 30 minutes of emergency duration. Optional 90 or 120 minute duration battery is available. Solid state charger & transfer. Standard with 120/347VAC input and consumes only 2W nominal power. BRUNO signs configured for AC/DC operation feature a universal 2 wire DC input; 6VDC - 24VDC. If an AC generator is used to back up the signs, a surge suppression device is recommended to protect the entire emergency circuit.

BELUCE AUTO-TEST (AT)

The BeLuce auto-test system automatically performs one 5 minute discharge test monthly and every 6 months it performs two 30 minute discharge tests, 24 hours apart. This tests both full battery capacity and recharge capability.

ORDERING GUIDE

BRU-RM - - - - -

SERIES	OPERATION	LIGHT SOURCE	FACE#	PICTOGRAMME	MOUNTING	OPTIONS
BRU-RM	Blank (AC only) SP (Self-powered)	L (LED)	¹ U (Universal) 1 (Single) 2 (Double)	OLR (Universal Pictogramme) O (No Indicators) L (Left Indicator) R (Right Indicator) D (Down Indicator) U (Up Indicator) UR (45° Up Right) DR (45° Down Right) UL (45° Up Left) DL (45° Down Left)	M (Universal) S (Surface) R (Recessed)	BA (Brushed aluminum finish) AT (Auto-test, SP only) PK12 (12" pendant kit) UDC (Universal 6 - 24VDC) 90SP (90 min. emergency) 120SP (120 min. emergency) ² FL (Visual alarm) ³ 120VDC (Specify 2 or 4 wires) IF(Inverted face) CC (Custom colour - specify)

NOTE: Order 50001132(Surface Mount Kit), 50001133(Recessed Mount Kit) if mounting needs to be changed on site. ¹Order OLR or 2 pictograms; ²Visual alarm only with AT option; ³With 120 VAC only.



BRUNO RM

Universal Edge-Lit Running Man

DIMENSIONS

