



# OTTICA ECO RM

Cylindrical Designed Edge-Lit Running Man

Project Name: \_\_\_\_\_

Model Number: \_\_\_\_\_

Prepared By: \_\_\_\_\_

Date: \_\_\_\_\_

## FEATURES & BENEFITS

- ABS cylindrical design
- Edge-lit LED technology
- AC Only, Self-Powered or Universal DC
- Surface wall or ceiling mounting
- Operating temperature: 0°C to 40°C
- GSA 22.2 No. 141-15 Performance Certified

## EXTERNAL SPECIFICATIONS

The OTTICA ECO ABS cylindrical housing is constructed as a single piece. The high clarity faceplate comes with both single face or double face versions. Smooth white finish is standard on all versions. External LED monitor light and test switch are standard on self-powered versions.

## INTERNAL SPECIFICATIONS

AC ONLY, AC/DC and SELF-POWERED: comes standard configured with high-output LED technology and 120/347VAC input. Nickel-cadmium batteries provide a minimum 90 minutes of emergency duration. OTTICA ECO exits configured for AC/DC operation feature a universal 2 wire DC output; 6V DC - 24V DC backup voltages are all field selectable.

## ELECTRICAL SPECIFICATIONS

If an AC generator is used to back up the signs, a surge suppression device is recommended to protect the entire emergency circuit.

## BATTERY TECHNOLOGY

The OTTICA ECO-SP is designed with a maintenance free, nickel-cadmium battery providing a minimum emergency duration of 90 minutes. Recharge time of the battery is 24 hours.

## UNIVERSAL PICTOGRAMS

The OLR(Universal) option includes: a pictogram with no directional indicators, a pictogram with a left facing directional indicator and a pictogram with a right facing directional indicator.

## ORDERING GUIDE

OT-ECO-RM - - - - -

SERIES	OPERATION	FACE#	PICTOGRAM	MOUNTING (SURFACE)	OPTIONS
OT-ECO-RM	Blank (AC only) SP (Self-powered)	U (Universal faces)	OLR (Universal pictogram)	M (Wall & Ceiling)	UDC (Universal 6 - 24VDC)

## DIMENSIONS

