HAZARDOUS

WET
NEMA 4X

PLURALUCE® HZ REMOTE

Hazardous 12-24V compact LED remote

Project Name: _____ Model Number: _____

Prepared By: _____ Date: _____

FEATURES & BENEFITS

- Up to 55' spacing on centre
- Die-cast aluminum cover
- NEMA 4X rated
- Operating Temperature: -30°C to +40°C
- 4 x 2.5W LEDs 4,000K
- 3 interchangeable lenses for symmetric or asymmetric ceiling or wall distribution
- Class I, Div 2, Groups A-D; Class II, Div 2, Groups E-G; Class III; T4 Class I, Zone 2, Group IIC, T4; Zone 22, Group IIIB
- CSA 22.2 No. 141-15 Performance Certified

LENSES

The **PLURALUCE® HZ** surface is supplied with 3 lenses for a choice of distribution patterns. These custom designed lenses are constructed of optical grade polycarbonate. The symmetrical ceiling distribution is suitable for use in open areas with spacing of up to 28' on centre. The asymmetcial ceiling distribution is designed for use in hallways and corridors with spacing of up to 55' on centre. The asymmetrical wall distribution provides 35' on centre with a 6' wide path of egress.

DIMENSIONS



Without mounting straps



With mounting straps

ORDERING GUIDE

PL-HZ-RMT - [ ]

SERIES	OPTIONS
PL-HZ-RMT	BA (Brushed aluminum housing) CC (Custom coloured housing) TP (Tamper proof screw) WG (Wireguard)