



STELLALUCE COMBO RM


Steel Running Man LED Combo

Project Name: _____ Model Number: _____
Prepared By: _____ Date: _____

FEATURES & BENEFITS

- Wall, ceiling or end mounting
- 3 interchangeable lenses for different light distribution
- High-output LED technology with constant light output level
- Integrated test button & LED indicator
- 2-wire universal AC input of 120-347 VAC
- 4 x 2.5W LEDs 4000K
- 20 gauge steel with a die-cast aluminum combo housing
- Operating temperature: +10°C to +40°C
- CSA 22.2 No. 141-15 Performance Certified

DIMENSIONS



AC INPUT RATINGS

VOLTAGE (VAC)	WATTAGE (W)	RATED CURRENT (A)
120/277/347	6.0/6.5/8.6	0.15/0.075/0.10


ORDERING GUIDE

SL-RM-PL - - - - -

SERIES	WATTS	LIGHT SOURCE	FACE#	PICTOGRAM	MOUNTING	OPTIONS
SL-RM-PL	12-10	L (LED)	1 (Single) 12 (Double) 2U (Universal)	OLR (Universal pictograms) 0 (No indicators) L (Left indicator) R (Right indicator) D (Down indicator) U (Up indicator) UR (45° up right) DR (45° down right) UL (45° up left) DL (45° down left)	3W (Wall) C (Ceiling) M (Universal mount)	CC (Custom colour - specify) WG (Wireguard) PK12 (12" pendant kit) AT (Auto-test) TP (Tamper proof screws) 90MIN (90 min. run time) 120MIN (120 min. run time)

NOTE: *Two pictograms or OLR must be specified; *OLR pictograms will be provided; *Single face only

LENS DISTRIBUTION PATTERNS



Reflectance percentage: 80/50/20, measurements are not to scale

LED TECHNOLOGY

The **STELLALUCE** is illuminated with four 2.5W Samsung LEDs. The **STELLALUCE** delivers up to 900 lm. Each pair of LEDs are laid out in parallel on the LED module so if one pair fails, the other will remain illuminated. A high-efficiency LED driver is used to maintain a constant output current to all LEDs. The LEDs are rated for >54,000 hours at L80.

BATTERY TECHNOLOGY

The **STELLALUCE** comes standard with a Ni-Cd battery pack that provides a minimum of 30 minute emergency duration. Optional 90 or 120 minute run time is available.

BELUCE AUTO-TEST (AT)

The system automatically performs one 5 minute discharge test monthly and every 6 months it performs two full discharge tests, 24 hours apart. This tests both full battery capacity and recharge capability. A manual Test feature is included when the Auto-test option is selected. The manual test will run a 30 second, 15 minute or 90 minute test by pressing the correct sequence of the test switch.

UNIVERSAL PICTOGRAMS

The OLR(Universal) option includes: a pictogram with no directional indicators, a pictogram with a left facing directional indicator and a pictogram with a right facing directional indicator.

