

Maximum Mounting Height Table

	SOURCE	PRODUCT	BASE	VOLTAGE (V)	WATTAGE (W)	LAMP PART NUMBER	OUTPUT (LM)	MAX. MOUNTING HEIGHT (FT)			
INCANDESCENT	TUNGSTEN	AR, LR, HDZ-RMT, SR, VR,WR	WEDGE	6	7.2	50405	86	20			
					9	50400	119	21			
				12	9	50402	133	19			
					12	BLUC-576000048	86	23			
					18	50404	199	25			
					24	9	LIT024V009WW	113	20		
	24	18	LIT024018W	239	33						
		QUARTZ	AR, LR, HDZ-RMT, SR, VR,WR	BI-PIN, (H3)	6	12	13631	178	24		
						12	12	13626	252	29	
	12				20	13625	299	66			
		55 (H3)	BLUC-576000109	381	31						
	MR16	BOL, BRV, BTMR, FTZ-C, RMR, SEA, SR, VR,WR	BI-PIN	12	20	BLUC-576000111	302	18			
					35	BLUC-576000128	377	54			
					50	50893	583	66			
	LED	MR16	BOL, BRV, BTMR, FTZ-C, RMR, SEA, SR,VR, WR	BI-PIN (LED)	6	5	BLUC-576000706	466	40		
7						BLUC-576000702	533	42			
12					2	BLUC-576000563	184	31			
					5	BLUC-576000706	466	40			
					7	BLUC-576000701	582	47			
					7	BLUC-576000703	647	48			
24					5	BLUC-576000706	466	40			
					5	BLUC-576000701	570	47			
					7	BLUC-567000703	647	48			
PAR36 (SEALED BEAM)					AR, LR	GX5.3 SCREW TERMINAL	12	6	BLUC-576000576	434	71
TESTA (SQUARE)					TES	2 WIRE CONNECTION	12	5	IHO-12-24V5W-BK	639	65
								9	IHO-12-24V9W-BK	1100	85
		14	IHO-12-24V14W-BK	1454				98			
		24	5	IHO-12-24V5W-BK			656	65			
			9	IHO-12-24V9W-BK			1110	83			
	12~24	14	IHO-12-24V14W-BK	1481			99				
		30	BLUC-576000579	2578			140				

IES/Photometrics are available for download on product pages.